



## Helgjenget stag

### Typer

DIN 975

### Materiale

Syrefast A4 - kl. 70.

### Teknisk data

Bruddgrense: 700N/mm<sup>2</sup>

Flytegrense Rp 0.2: 450N/mm<sup>2</sup>

| Dim<br>[mm] | Arbeidslast<br>[kN] | Bruddlast<br>[kg] | Vekt<br>[kg] | Ant/pk<br>[stk] | Varenr    |
|-------------|---------------------|-------------------|--------------|-----------------|-----------|
| M6 x 1000   | 9,0                 | 14,1              | 0.180        | 1               | 3441859 * |
| M8 x 1000   | 16,5                | 25,6              | 0.320        | 1               | 3441863   |
| M10 x 1000  | 26,1                | 40,6              | 0.500        | 1               | 3441866   |
| M12 x 1000  | 37,9                | 59,0              | 0.740        | 1               | 3441869   |
| M16 x 1000  | 70,6                | 110,0             | 1.340        | 1               | 3441873   |
| M20 x 1000  | 110,2               | 171,5             | 2.100        | 1               | 3441876 * |
| M8 x 2000   | 16,5                | 25,6              | 0.640        | 1               | 3441913   |
| M10 x 2000  | 26,1                | 40,6              | 1.000        | 1               | 3441916   |
| M12 x 2000  | 37,9                | 59,0              | 1.460        | 1               | 3441919 * |
| M16 x 2000  | 70,6                | 110,0             | 2.680        | 1               | 3441923 * |

\* Bestillingsvare