

Overgang Stabil innv. gjenge

Bruksområde

Overgang innv. gjenge brukes som overgang fra Multi-Gjenget 3G anslutnings-mutter til andre gjengede detaljer.

Materiale

Type A: Stål

Type B: Aduserjern

Elektroforsinket 12



M16-M12



M16-M12



1" / 3/8"



1" / 3/8"

Dim	Type [mm]	L [mm]	Nøkkelvidde [mm]	Vekt [kg]	Ant/pk [stk]	Varenr	
M16 / M10	A	35	19	0.046	50	3446451	*
M16 / M12	A	35	19	0.043	50	3446453	
M16 / M16	A	30	19	0.030	50	3441193	*
3/8" / M16	A	35	19	0.040	25	3446461	*
1/2" / M10	A	35	24	0.070	10	3446469	*
1/2" / M12	A	35	24	0.070	10	3442609	
1/2" / M16	A	40	24	0.073	25	3446455	*
1/2" / 1/2"	B	35	27	0.060	10	3446471	*
3/4" / M10	B	35	22	0.120	10	3441194	*
3/4" / M12	B	35	22	0.110	10	3441195	*
3/4" / M16	B	35	22	0.070	10	3446457	*
3/4" / 3/8"	B	35	22	0.080	25	3446465	*
3/4" / 1/2"	B	35	27	0.920	10	3446473	*
1" / M10	B	40	22	0.132	10	3442611	*
1" / M12	B	40	22	0.130	10	3442612	*
1" / M16	B	40	22	0.410	10	3446459	*
1" / 3/8"	B	40	22	0.130	25	3446467	*
1" / 1/2"	B	40	27	0.150	10	3446475	*

* Bestillingsvare