

Dimensjon og vekt, stålrør NS-EN 10220 (Sveiset)

Nom. dia. [DN]	Utv. dia. [mm]	Rørtykk. [mm]	Rørvekt [kg/m]	Vanninh. [L/m]	Rør + Vann [kg/m]	Klammeravstand uisolert rør [m]
	10,2	1,60	0,340	0,040	0,380	
10,0	13,5	1,80	0,520	0,080	0,600	1,00
	16,0	1,80	0,630	0,120	0,750	
	17,2	1,80	0,680	0,150	0,830	
	19,0	2,00	0,840	0,180	1,020	
15,0	20,0	2,00	0,890	0,200	1,090	1,20
	21,3	2,00	0,950	0,240	1,190	
20,0	25,0	2,00	1,130	0,350	1,480	1,40
	25,4	2,00	1,150	0,360	1,510	
	26,9	2,00	1,230	0,410	1,640	
25,0	30,0	2,00	1,380	0,530	1,910	1,80
	31,8	2,00	1,470	0,610	2,080	
	33,7	2,00	1,560	0,690	2,250	
32,0	38,0	2,30	2,020	0,880	2,900	2,20
	42,4	2,30	2,270	1,120	3,390	
40,0	44,5	2,30	2,390	1,250	3,640	2,40
	48,3	2,30	2,610	1,500	4,110	
	51,0	2,30	2,760	1,690	4,450	
	54,0	2,30	2,930	1,920	4,850	
50,0	57,0	2,30	3,100	2,160	5,260	3,10
	60,3	2,30	3,290	2,440	5,730	
	63,5	2,60	3,900	2,670	6,570	
	70,0	2,60	4,320	3,300	7,620	
	73,0	2,60	4,510	3,610	8,120	
65,0	76,1	2,60	4,710	3,950	8,660	3,30
	82,5	2,60	5,120	4,690	9,810	
80,0	88,9	2,90	6,150	5,420	11,570	4,20
	101,6	2,90	7,060	7,210	14,270	
100,0	108,0	2,90	7,520	8,200	15,720	4,50
	114,3	3,20	8,770	9,140	17,910	
	127,0	3,20	9,770	11,420	21,190	
125,0	133,0	3,60	11,490	12,430	23,920	5,10
	139,7	3,60	12,080	13,790	25,870	
	152,4	4,00	14,640	16,380	31,020	
150,0	159,0	4,00	15,290	17,910	33,200	5,80
	168,3	4,00	16,210	20,180	36,390	
	177,8	4,50	19,230	22,380	41,610	
	193,7	4,50	21,000	26,790	47,790	
200,0	219,1	4,50	23,820	34,670	58,490	7,80
	244,5	5,00	29,530	43,190	72,720	
	273,0	5,00	33,050	54,330	87,380	
	323,9	5,60	43,960	76,800	120,760	
	355,6	5,60	48,340	93,160	141,500	
	406,4	6,30	62,16	121,80	183,960	
	457,0	6,30	70,020	155,100	225,120	
	508,0	6,30	77,950	192,750	270,700	
	559,0	6,30	85,870	234,480	320,350	
	610,0	6,30	93,800	280,300	374,100	